GDB QUICK REFERENCE GDB Version 5

Essential Commands

gdb *program* [*core*]	debug *program* [using coredump *core*]
b [*file*:]*function*	set breakpoint at *function* [in *file*]
run [*arglist*]	start your program [with *arglist*]
bt	backtrace: display program stack
p *expr*	display the value of an expression
c	continue running your program
n	next line, stepping over function calls
s	next line, stepping into function calls

Starting GDB

gdb	start GDB, with no debugging files
gdb *program*	begin debugging *program*
gdb *program core*	debug coredump *core* produced by *program*
gdb --help	describe command line options

Stopping GDB

quit	exit GDB; also q or EOF (eg C-d)
INTERRUPT	(eg C-c) terminate current command, or send to running process

Getting Help

help	list classes of commands
help *class*	one-line descriptions for commands in *class*
help *command*	describe *command*

Executing your Program

run *arglist*	start your program with *arglist*
run	start your program with current argument list
run ... <*inf* >*outf*	start your program with input, output redirected
kill	kill running program
tty *dev*	use *dev* as stdin and stdout for next **run**
set args *arglist*	specify *arglist* for next **run**
set args	specify empty argument list
show args	display argument list
show env	show all environment variables
show env *var*	show value of environment variable *var*
set env *var string*	set environment variable *var*
unset env *var*	remove *var* from environment

Shell Commands

cd *dir*	change working directory to *dir*
pwd	Print working directory
make ...	call "make"
shell *cmd*	execute arbitrary shell command string

[ ] surround optional arguments ... show one or more arguments

Breakpoints and Watchpoints

break [*file*:]*line* b [*file*:]*line*	set breakpoint at *line* number [in *file*] eg: break main.c:37
break [*file*:]*func*	set breakpoint at *func* [in *file*]
break +*offset* break -*offset*	set break at *offset* lines from current stop
break **addr*	set breakpoint at address *addr*
break	set breakpoint at next instruction
break ... if *expr*	break conditionally on nonzero *expr*
cond *n* [*expr*]	new conditional expression on breakpoint *n*; make unconditional if no *expr*
tbreak ...	temporary break; disable when reached
rbreak [*file*:]*regex*	break on all functions matching *regex* [in *file*]
watch *expr*	set a watchpoint for expression *expr*
catch *event*	break at *event*, which may be **catch**, **throw**, **exec**, **fork**, **vfork**, **load**, or **unload**.
info break	show defined breakpoints
info watch	show defined watchpoints
clear	delete breakpoints at next instruction
clear [*file*:]*fun*	delete breakpoints at entry to *fun*()
clear [*file*:]*line*	delete breakpoints on source line
delete [*n*]	delete breakpoints [or breakpoint *n*]
disable [*n*]	disable breakpoints [or breakpoint *n*]
enable [*n*]	enable breakpoints [or breakpoint *n*]
enable once [*n*]	enable breakpoints [or breakpoint *n*]; disable again when reached
enable del [*n*]	enable breakpoints [or breakpoint *n*]; delete when reached
ignore *n count*	ignore breakpoint *n*, *count* times
commands *n* [silent] *command-list*	execute GDB *command-list* every time breakpoint *n* is reached. [**silent** suppresses default display]
end	end of *command-list*

Program Stack

backtrace [*n*] bt [*n*]	print trace of all frames in stack; or of *n* frames—innermost if *n*>0, outermost if *n*<0
frame [*n*]	select frame number *n* or frame at address *n*; if no *n*, display current frame
up *n*	select frame *n* frames up
down *n*	select frame *n* frames down
info frame [*addr*]	describe selected frame, or frame at *addr*
info args	arguments of selected frame
info locals	local variables of selected frame
info reg [*rn*]...	register values [for regs *rn*] in selected frame; **all-reg** includes floating point
info all-reg [*rn*]	

Execution Control

continue [*count*] c [*count*]	continue running; if *count* specified, ignore this breakpoint next *count* times
step [*count*] s [*count*]	execute until another line reached; repeat *count* times if specified
stepi [*count*] si [*count*]	step by machine instructions rather than source lines
next [*count*] n [*count*]	execute next line, including any function calls
nexti [*count*] ni [*count*]	next machine instruction rather than source line
until [*location*]	run until next instruction (or *location*)
finish	run until selected stack frame returns
return [*expr*]	pop selected stack frame without executing [setting return value]
signal *num*	resume execution with signal *s* (none if 0)
jump *line* jump **address*	resume execution at specified *line* number or *address*
set var=*expr*	evaluate *expr* without displaying it; use for altering program variables

Display

print [/*f*] [*expr*] p [/*f*] [*expr*]	show value of *expr* [or last value $] according to format *f*:
x	hexadecimal
d	signed decimal
u	unsigned decimal
o	octal
t	binary
a	address, absolute and relative
c	character
f	floating point
call [/*f*] *expr*	like **print** but does not display **void**
x [/*Nuf*] *expr*	examine memory at address *expr*; optional format spec follows slash
N	count of how many units to display
u	unit size; one of **b** individual bytes **h** halfwords (two bytes) **w** words (four bytes) **g** giant words (eight bytes)
f	printing format. Any **print** format, or **s** null-terminated string **i** machine instructions
disassem [*addr*]	display memory as machine instructions

Automatic Display

display [/*f*] *expr*	show value of *expr* each time program stops [according to format *f*]
display	display all enabled expressions on list
undisplay *n*	remove number(s) *n* from list of automatically displayed expressions
disable disp *n*	disable display for expression(s) number *n*
enable disp *n*	enable display for expression(s) number *n*
info display	numbered list of display expressions

Expressions

expr	an expression in C, C++, or Modula-2 (including function calls), or:
addr@*len*	an array of *len* elements beginning at *addr*
file::*nm*	a variable or function *nm* defined in *file*
{*type*}*addr*	read memory at *addr* as specified *type*
`$`	most recent displayed value
`$`*n*	*n*th displayed value
`$$`	displayed value previous to $
`$$`*n*	*n*th displayed value back from $
`$_`	last address examined with `x`
`$__`	value at address $_
`$`*var*	convenience variable; assign any value
`show values` [*n*]	show last 10 values [or surrounding $*n*]
`show conv`	display all convenience variables

Symbol Table

`info address` *s*	show where symbol *s* is stored
`info func` [*regex*]	show names, types of defined functions (all, or matching *regex*)
`info var` [*regex*]	show names, types of global variables (all, or matching *regex*)
`whatis` [*expr*]	show data type of *expr* [or `$`] without evaluating; `ptype` gives more detail
`ptype` [*expr*]	
`ptype` *type*	describe type, struct, union, or enum

GDB Scripts

`source` *script*	read, execute GDB commands from file *script*
`define` *cmd* *command-list*	create new GDB command *cmd*; execute script defined by *command-list*
`end`	end of *command-list*
`document` *cmd* *help-text*	create online documentation for new GDB command *cmd*
`end`	end of *help-text*

Signals

`handle` *signal act*	specify GDB actions for *signal*:
`print`	announce signal
`noprint`	be silent for signal
`stop`	halt execution on signal
`nostop`	do not halt execution
`pass`	allow your program to handle signal
`nopass`	do not allow your program to see signal
`info signals`	show table of signals, GDB action for each

Debugging Targets

`target` *type param*	connect to target machine, process, or file
`help target`	display available targets
`attach` *param*	connect to another process
`detach`	release target from GDB control

Controlling GDB

`set` *param value*	set one of GDB's internal parameters
`show` *param*	display current setting of parameter

Parameters understood by `set` and `show`:

`complaint` *limit*	number of messages on unusual symbols
`confirm` *on/off*	enable or disable cautionary queries
`editing` *on/off*	control `readline` command-line editing
`height` *lpp*	number of lines before pause in display
`language` *lang*	Language for GDB expressions (`auto`, `c` or `modula-2`)
`listsize` *n*	number of lines shown by `list`
`prompt` *str*	use *str* as GDB prompt
`radix` *base*	octal, decimal, or hex number representation
`verbose` *on/off*	control messages when loading symbols
`width` *cpl*	number of characters before line folded
`write` *on/off*	Allow or forbid patching binary, core files (when reopened with `exec` or `core`)
`history ...`	groups with the following options:
`h ...`	
`h exp` *off/on*	disable/enable `readline` history expansion
`h file` *filename*	file for recording GDB command history
`h size` *size*	number of commands kept in history list
`h save` *off/on*	control use of external file for command history
`print ...`	groups with the following options:
`p ...`	
`p address` *on/off*	print memory addresses in stacks, values
`p array` *off/on*	compact or attractive format for arrays
`p demangl` *on/off*	source (demangled) or internal form for C++ symbols
`p asm-dem` *on/off*	demangle C++ symbols in machine-instruction output
`p elements` *limit*	number of array elements to display
`p object` *on/off*	print C++ derived types for objects
`p pretty` *off/on*	struct display: compact or indented
`p union` *on/off*	display of union members
`p vtbl` *off/on*	display of C++ virtual function tables

`show commands`	show last 10 commands
`show commands` *n*	show 10 commands around number *n*
`show commands +`	show next 10 commands

Working Files

`file` [*file*]	use *file* for both symbols and executable; with no arg, discard both
`core` [*file*]	read *file* as coredump; or discard
`exec` [*file*]	use *file* as executable only; or discard
`symbol` [*file*]	use symbol table from *file*; or discard
`load` *file*	dynamically link *file* and add its symbols
`add-sym` *file addr*	read additional symbols from *file*, dynamically loaded at *addr*
`info files`	display working files and targets in use
`path` *dirs*	add *dirs* to front of path searched for executable and symbol files
`show path`	display executable and symbol file path
`info share`	list names of shared libraries currently loaded

Source Files

`dir` *names*	add directory *names* to front of source path
`dir`	clear source path
`show dir`	show current source path
`list`	show next ten lines of source
`list -`	show previous ten lines
`list` *lines*	display source surrounding *lines*, specified as:
[*file*:]*num*	line number [in named file]
[*file*:]*function*	beginning of function [in named file]
`+`*off*	*off* lines after last printed
`-`*off*	*off* lines previous to last printed
`*`*address*	line containing *address*
`list` *f*,*l*	from line *f* to line *l*
`info line` *num*	show starting, ending addresses of compiled code for source line *num*
`info source`	show name of current source file
`info sources`	list all source files in use
`forw` *regex*	search following source lines for *regex*
`rev` *regex*	search preceding source lines for *regex*

GDB under GNU Emacs

`M-x gdb`	run GDB under Emacs
`C-h m`	describe GDB mode
`M-s`	step one line (`step`)
`M-n`	next line (`next`)
`M-i`	step one instruction (`stepi`)
`C-c C-f`	finish current stack frame (`finish`)
`M-c`	continue (`cont`)
`M-u`	up *arg* frames (`up`)
`M-d`	down *arg* frames (`down`)
`C-x &`	copy number from point, insert at end
`C-x SPC`	(in source file) set break at point

GDB License

`show copying`	Display GNU General Public License
`show warranty`	There is NO WARRANTY for GDB. Display full no-warranty statement.